

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (original) An instant printer comprising an exposure device for projecting printing light based on image data, and a pair of spread rollers, wherein the instant printer records a latent image in an exposure area of a predetermined size on an instant film that includes a processing fluid, by exposing the instant film to the printing light, and develops the latent image into a positive image by spreading the processing fluid over the exposed instant film through the spread rollers, characterized in that:

the exposure device comprises a printing head for projecting the printing light linearly along a main scan direction, and a scanning mechanism for moving the printing head relative to the instant film in a sub scan direction perpendicular to the main scan direction, wherein an illumination range of the printing light by the printing head is longer in the main scan direction than a length in the main scan direction of the exposure area, whereas a sub scanning range by the scanning mechanism is longer than a length in the sub scan direction of the exposure area.

2. (original) An instant printer according to claim 1, wherein the instant film is contained in a case that is formed with an exposure opening for exposing the exposure area, and the size of the illumination range relative to the exposure area is determined in accordance with clearances provided between the case and the instant film.

3. (original) An instant printer according to claim 2, wherein the printing head is at least partly inserted in the exposure opening.

4. (original) An instant printer according to claim 3, wherein the exposure opening is larger than the exposure area, whereas the illumination range of the printing head is confined in the exposure opening when the case is loaded in a loading chamber.

5. (original) An instant printer according to claim 1, wherein the printing head is moved from a scanning start position that is located before the exposure area in the sub scan direction, to a scanning end position that is beyond the exposure area in the sub scan direction, and is driven based on image data

of one frame line sequentially from the scanning start position to the scanning end position, to accomplish one sub scanning.

6. (original) An instant printer according to claim 5, wherein the printing head is designed to record a number of pixels along a line extending in the main scan direction, the number being more than a necessary number for recording pixels through the entire length of the exposure area in the main scan direction, and wherein drive data corresponding to the pixels of one line recorded by the printing head is produced from the image data.

7. (original) An instant printer according to claim 1, further comprising a device for connecting an external memory to the instant printer, and a device for reading out image data stored in the external memory, wherein the exposure device may be driven based on the image data read out from the external memory.

8. (original) An instant printer according to claim 7, further comprising an imaging device for photographing a subject, wherein an image of a subject photographed through the imaging device is recorded on the instant film by driving the exposure device based on image data obtained from the imaging device.

9. (original) An instant printer according to claim 8, further comprising a device for compressing image data of a subject photographed through the imaging device and writing it on the external memory, and a device for expanding compressed image data as it is read out from the external memory, wherein the exposure device may be driven based on the expanded image data.

10. (original) An instant printer according to claim 9, further comprising a device for synthesizing image data read out from the external memory with image data photographed through the imaging device, wherein the exposure device may be driven based on the synthesized image data.

11. (original) A printing method for recording a latent image in an exposure area of a predetermined size on an instant film that includes a processing fluid, by projecting printing light from an exposure device onto the instant film based on image data, and developing the latent image into a positive image by spreading the processing fluid over the exposed instant film through a pair of spread rollers, characterized in that:

an illumination range of the printing light on the instant film by the exposure device is determined to be larger

than the exposure area, so the entire exposure area may be exposed even where the instant film deviates from a predetermined position relative to the exposure device.

12. (original) A printing method according to claim 11, wherein the instant film is contained in a case that is formed with an exposure opening for exposing the exposure area, and the size of the illumination range relative to the exposure area is determined in accordance with clearances provided between the case and the instant film.

13. (currently amended) In an ~~An~~ instant printer comprising a loading chamber for loading a plurality of instant films that include a processing fluid, a printing head for projecting printing light onto a photosensitive surface of the loaded instant film on the basis of image data, a scanning mechanism for moving the printing head along the photosensitive surface of the instant film, a pair of spread rollers for spreading the processing fluid over the exposed instant film, and a body for containing the above elements, the ~~instant printer~~ being characterized in that improvement comprising:

a light-shielding housing provided inside the body, that  
~~covers~~ the light-shielding housing covering up at least a moving

range of the printing head in a light-tight fashion ~~is provided inside the body.~~

14. (original) An instant printer according to claim 13, wherein the light-shielding housing covers up the scanning mechanism besides the moving range of the printing head.

15. (original) An instant printer according to claim 13, wherein the light-shielding housing is formed integrally with the loading chamber.

16. (currently amended) In an ~~An~~ electronic still camera comprising an imaging device for obtaining image data by photographing a subject, a loading chamber for loading a plurality of instant films that include a processing fluid, a printing head for projecting printing light onto a photosensitive surface of the loaded instant film on the basis of image data, a scanning mechanism for moving the printing head along the photosensitive surface of the instant film, a pair of spread rollers for spreading the processing fluid over the exposed instant film, and a camera body for containing the above elements, the ~~electronic still camera being characterized in that~~ improvement comprising:

a light-shielding housing provided inside the camera body, that covers the light-shielding housing covering up at least a moving range of the printing head in a light-tight fashion ~~is provided inside the camera body.~~

17-20. (canceled)

21. (previously presented) The instant printer of claim 1, wherein a photosensitive area of the instant film has dimensions less than overall dimensions of the instant film, so that the exposure area cannot extend to outer boundaries of the instant film.

22. (previously presented) The printing method of claim 11, wherein a photosensitive area of the instant film has dimensions less than overall dimensions of the instant film, so that the exposure area cannot extend to outer boundaries of the instant film.